



# Industrial Linings, Inc.

8475 Bellingrath Road  
Phone: 251-653-5052

PO Box 190580  
Fax: 251-653-7367

Mobile, AL 36619  
Toll Free: 800-350-0795

## **MAXIMUM PIPE HANGER SPACING AT PRESSURE RATING**

The table below is based on non-insulated pipe containing liquids having a specific gravity of 1.3 and at a maximum temperature of 180° F. For services at temperature above 180° F, reduce hanger spacing 3% for every 20° F elevation in temperature.

<b>PIPE ID Inches</b>	<b>25 PSI Feet</b>	<b>50 PSI Feet</b>	<b>75 PSI Feet</b>	<b>100 PSI Feet</b>	<b>125 PSI Feet</b>	<b>150 PSI Feet</b>
<b>2</b>	6.0	6.0	6.0	6.0	6.0	6.0
<b>3</b>	6.5	6.5	6.5	6.5	8.0	8.0
<b>4</b>	7.0	7.0	7.0	8.5	8.5	8.5
<b>6</b>	8.0	8.0	9.0	9.0	10.0	10.5
<b>8</b>	8.5	10.0	10.0	10.5	11.0	11.5
<b>10</b>	9.5	10.5	11.5	12.0	12.5	13.0
<b>12</b>	10.0	11.5	12.5	13.0	13.5	14.0
<b>14</b>	11.5	12.5	13.0	14.0	15.0	15.5
<b>16</b>	12.0	13.0	14.0	15.5	16.5	17.0
<b>18</b>	12.5	14.5	15.0	16.0	16.5	17.5
<b>20</b>	12.5	15.0	15.5	17.0	18.0	18.5
<b>24</b>	8.5	15.0	17.0	18.5	19.0	
<b>30</b>	9.5	17.5	19.5	21.0		
<b>36</b>	10.5	19.5	21.0			
<b>42</b>	8.0	21.0	22.5			