



Industrial Linings, Inc.

8475 Bellingrath Road
Phone: 251-653-5052

PO Box 190580
Fax: 251-653-7367

Mobile, AL 36619
Toll Free: 800-350-0795

MAXIMUM PIPE HANGER SPACING AT PRESSURE RATING

The table below is based on non-insulated pipe containing liquids having a specific gravity of 1.3 and at a maximum temperature of 180° F. For services at temperature above 180° F, reduce hanger spacing 3% for every 20° F elevation in temperature.

PIPE ID Inches	25 PSI Feet	50 PSI Feet	75 PSI Feet	100 PSI Feet	125 PSI Feet	150 PSI Feet
2	6.0	6.0	6.0	6.0	6.0	6.0
3	6.5	6.5	6.5	6.5	8.0	8.0
4	7.0	7.0	7.0	8.5	8.5	8.5
6	8.0	8.0	9.0	9.0	10.0	10.5
8	8.5	10.0	10.0	10.5	11.0	11.5
10	9.5	10.5	11.5	12.0	12.5	13.0
12	10.0	11.5	12.5	13.0	13.5	14.0
14	11.5	12.5	13.0	14.0	15.0	15.5
16	12.0	13.0	14.0	15.5	16.5	17.0
18	12.5	14.5	15.0	16.0	16.5	17.5
20	12.5	15.0	15.5	17.0	18.0	18.5
24	8.5	15.0	17.0	18.5	19.0	
30	9.5	17.5	19.5	21.0		
36	10.5	19.5	21.0			
42	8.0	21.0	22.5			